





















Navedene cene su bez PDV-a. Radi ostvarivanja **POPUSTA, kontaktirajte nas!**

Proizvođač	Opis	Ident	Cena	Foto
IP kolor kamere				
Videosec	Unutrašnja IP 3-Axis Dome Camera, 1.3M progressive sensor, fiksna optika HD Lens: 2.8mm/F2.0, Max. 1280*1024 Stream, H.264/MPEG4/MJPEG Tri-CODEC, 2-way audio, SDK: AXIS like API/CGI (Open API for software integration), isporučuje se sa NUUO IP-P LITE Licence, 12VDC / PoE	VDS-ID-209	99.99	
Videosec	Unutrašnja IP Dome Camera, 2.1Mpix. full HD progressive 1/2.7" CMOS sensor, 12.5fps 1920x1080p (single stream), 25fps 1280x720p (dual stream), H.264/MJPEG, fiksna optika 4mm/F1.5, 0.02Lux, 1-way audio, Motion Detection, Privacy Masks, Internet Explorer, Chrome, Fire Fox, Local SD Card and FTP Recording, support, isporučuje se sa NUUO IP-P LITE Licence, PoE only	VDS-ID-20	191.00	
Videosec	Antivandal IP 3-Axis dome Camera, 1.3M progressive sensor, Max. 1280*1024 Stream, H.264/MPEG4/MJPEG Tri-CODEC, Varifocal Lens	VDS-IDA-211	149.00	
Videosec	Kolor D&N bullet IP kamera (Infra Red ILLUMINATOR) - ICR (IR Cut filter change mechanism), 2.1Mpix. full HD progressive 1/2.7" CMOS sensor, Max. 1920x1080 (Dual Stream) H.264/MJPEG, support 25fps 1920x1080p (Dual Stream), Internet Explorer, Chrome, Fire Fox ,Auto Iris 3-9 mm/F1.2 Vari focal lens, Onvif 1.02-3 Firmware, DI/DO, RS485, podržava SD Card and FTP Recording, isporučuje se sa NUUO IP-P LITE Licence, 12VDC & AC24V & PoE	VDS-IRW-20W	487.00	
Videosec	Kolor D&N unutrašnja dome IP kamera (Infra Red ILLUMINATOR) - ICR (IR Cut filter change mechanism), 2.1Mpix. full HD progressive 1/2.7" CMOS sensor, Max. 1920x1080 (Dual Stream) H.264/MJPEG, support 25fps 1920x1080p (Dual Stream), Internet Explorer, Chrome, Fire Fox ,Auto Iris 3-9 mm/F1.2 Vari focal lens, Onvif 1.02-3 Firmware, DI/DO, RS485, podržava SD Card and FTP Recording, isporučuje se sa NUUO IP-P LITE Licence, 12VDC & AC24V & PoE	VDS-IRD-20W	462.00	
Videosec	Kolor D&N Box IP kamera - ICR (IR Cut filter change mechanism), 1.3Mpix. HD progressive 1/3" SONY CCD sensor, Max. 1280x960, 0.001Lux, H.264/MJPEG + BNC Video Output • 1280x960-15fps / 1280x720p-30fps, 2-way audio, Motion Detection, WDR (Wide Dynamic Range), 3DNR (Digital Noise Reduction), Privacy Masks, Internet Explorer, Chrome, Fire Fox ,HD kamere mogu da se koriste samo sa HD optikom (1/3" or 1/2"), podržava SD Card and FTP Recording, Onvif 1.02-3 Firmware, RS485, 12VDC/24VAC/PoE	VDS-ICS-13	199.00	
Videosec	Kolor D&N Box IP kamera - ICR (IR Cut filter change mechanism), 2.1Mpix. full HD progressive 1/2.7" CMOS sensor 1920x1080, 0.02Lux, H.264/MJPEG + BNC Video Output, 12.5fps 1920x1080p (single stream), 25fps 1280x720p (dual stream), 2-way audio, Motion Detection, Privacy Masks, Internet Explorer, Chrome, Fire Fox ,HD kamere mogu da se koriste samo sa HD optikom (1/3" or 1/2"), podržava SD Card and FTP Recording, Onvif 1.02-3 Firmware, DI/DO, RS485, 12VDC/PoE	VDS-ICS-20F	267.00	
Videosec	Kolor D&N Box IP kamera - ICR (IR Cut filter change mechanism), 2.1Mpix. full HD progressive 1/2.7" CMOS sensor 1920x1080, 0.02Lux, H.264/MJPEG + BNC Video Output, 30fps 1920x1080p (Dual Stream), 2-way audio, Motion Detection, Privacy Masks, Internet Explorer, Chrome, Fire Fox ,HD kamere mogu da se koriste samo sa HD optikom (1/3" or 1/2"), podržava SD Card and FTP Recording, Onvif 1.02-3 Firmware, DI/DO, RS485, 12VDC/PoE	VDS-ICS-20W	343.00	
Videosec	D&N Box IP Camera - ICR - WDR - DNR - 5Mpix 1/3.2" CMOS progressive sensor 2592X1944, H.264/MJPEG • Local SD Card and FTP Recording, support 10fps 2592X1944 (Single Stream) 5Mpix 20fps 2048X1536 (Single Stream) 3Mpix 25fps 1920x1080p (Dual Stream) 1080p • Onvif 1.02-3 Firmware, DI/DO, RS485, Power: 12VDC and PoE Attention: for Best Results recommended 5 Mpix Certified Lenses	VDS-ICS-50W	441.00	 
Videosec	D&N Box IP Camera - ICR - WDR - DNR - 5Mpix 1/3.2" CMOS progressive sensor 2592X1944, H.264/MJPEG • Local SD Card and FTP Recording, support 10fps 2592X1944 (Single Stream) 5Mpix 20fps 2048X1536 (Single Stream) 3Mpix 25fps 1920x1080p (Dual Stream) 1080p • Onvif 1.02-3 Firmware, DI/DO, RS485, Power: 12VDC and PoE Attention: for Best Results recommended 5 Mpix Certified Lenses	VDS-ICS-50WF	497.00	 





Softver za IP kamere i prateća oprema

Videosec	PC based Network Video Recording Software, Podržava 50 proizvođača I preko 1000 modela IP kamera, U direktnom prikazu može da prikaže do 64 kanala, 6 tipova analize za aktivaciju snimanja, Pregled snimljenog materijala 16 kanala, Napredna pretraga snimljenog materijala, Podržava više servera kod udaljenog pristupa, Udaljeni prikaz do 128 kanala, Udaljeni pregled snimljenog materijala 16 kanala, Prilagodljiv profil protoka, Podrška za pristup mobilnim telefonom, E-mape podržavaju do 10 "slojeva", Podrška za: Vodeni žig, POS, Aplikaciju za brojanje prolaza, CMS, SDK	NVR-PC Pro.	120.00	Recording License IP-P FULL version Price/Ch 120 EUR
Videosec	Recording License, IP-P LITE* version, U direktnom prikazu može da prikaže do 32 kanala, 2 tipa analize za aktivaciju snimanja (pokret, digitalni ulaz), Pregled snimljenog materijala 4 kanala, Podržava jedan server kod udaljenog pristupa, Udaljeni prikaz do 16 kanala, Udaljeni pregled snimljenog materijala 4 kanala, Fiksni profil protoka, Podrška za pristup mobilnim telefonom, E-mape podržavaju 1 "sloj", Podrška za vodeni žig	NVR-PC Lite	25.00	Recording License IP-P LITE* version Price/Ch 25 EUR

Stand Alone IP Network Video Recorder

Videosec	4Ch Stand Alone IP Network Video Recorder, podržava 33 proizvođača IP kamera i 1000 modela, podržava megapikselske kamere i H.264 compression format, NUUO Central Management System (CMS) podržava do 128CH live display, podržava 2xSATA II HDD, 2xUSB 2.0 (for UPS); External storage available in FW v2.4, Recording Performance: Total bitrate: 40Mbps, (1080p/60fps), LAN Transmission Speed 10/100/1000 Mbps (RJ45), Power: 100-240V - Max. 39W, Same Remote Live Viewer and CMS for PC Based (IP+) & Standalone NVRs, (can be connected All together in one common monitoring system)	VDS-NE-2040	1,029.00	 
Videosec	8Ch Stand Alone IP Network Video Recorder, podržava 33 proizvođača IP kamera i 1000 modela, podržava megapikselske kamere i H.264 compression format, NUUO Central Management System (CMS) podržava do 128CH live display, podržava 4xSATA II HDD, 2xUSB 2.0 (for UPS); External storage available in FW v2.4, Recording Performance: Total bitrate: 80Mbps, (1080p/120fps), LAN Transmission Speed 10/100/1000 Mbps (RJ45), Power: 100-240V - Max. 39W, Same Remote Live Viewer and CMS for PC Based (IP+) & Standalone NVRs, (can be connected All together in one common monitoring system)	VDS-NE-4080	1,923.00	 
Videosec	16Ch Stand Alone IP Network Video Recorder, podržava 33 proizvođača IP kamera i 1000 modela, podržava megapikselske kamere i H.264 compression format, NUUO Central Management System (CMS) podržava do 128CH live display, podržava 4xSATA II HDD, 2xUSB 2.0 (for UPS); External storage available in FW v2.4, Recording Performance: Total bitrate: 40Mbps, (1080p/120fps), LAN Transmission Speed 10/100/1000 Mbps (RJ45), Power: 100-240V - Max. 39W, Same Remote Live Viewer and CMS for PC Based (IP+) & Standalone NVRs, (can be connected All together in one common monitoring system)	VDS-NE-4160	2,699.00	 
Videosec	Hibridni DVR za 8 analognih kanala i 4 IP kanala, bez hard diska, podržava 8x SATA HDD, 8ch (D1/Real Time)+4ch-IP/25fps/1080p, 8 channel audio inputs, 8 channel loop outputs, H.264/MPEG4 kompresija, 2xUSB, Spot - Output, video, HDMI i VGA izlazi, 8x Alarm IN, 6x Alarm OUT, E-SATA connector, daljinski upravljač i miš	VDS-DVR-08HET-4H	787.00	 

Optike za IP kamere

FUJINON FUJIFILM	Megapikselska optika visoke rezolucije za megapikselske kamere rezolucije 3Mpix. DC Autoiris Varifocal 2.8-8mm/F1.2, CS MOUNT, Aspherical Lens 1/3" - Zero focus shift between day time and Infrared performance	YV2.8x2.8SA-SA2-L Megapixel	103.60	 
FUJINON FUJIFILM	Megapikselska optika visoke rezolucije za megapikselske kamere rezolucije do 3 Mpix. Manual iris Varifocal 3.8-13mm/F1.4, C MOUNT - 1/2", Aspherical Lens - Zero focus shift between day time and Infrared performance	DV3.4x3.8SA-1 Megapixel	105.60	 
Videosec	Megapikselska optika visoke rezolucije za megapikselske kamere rezolucije do 3 Mpix. DC Auto Iris Varifocal 2.8-12mm/F1.4, C MOUNT - 1/2", Aspherical Lens - Zero focus shift between day time and Infrared performance, IR Corrected	LVC-2812H Megapixel	108.00	