

Navedene cene su bez PDV-a. Radi ostvarivanja **POPUSTA, kontaktirajte nas!**

Proizvođač	Opis	Ident	Cena	Foto
Mobilni digitalni rekorderi				
	DVR za 1 kanal za ugradnju u vozila, podržava 1x2GB SD memory card (support SDHC), brzina prikaza/snimanja 30fps u rezoluciji 640*480 ili 320*240, JPEG kompresija, snimanje kontinualno, po događajima ili pritiskom na panik taster, G-senzor, RTC, PC program za analizu, sa integrisanom kamerom 1/4" CMOS Digital Sensor 310K pixels, Angle of View: 170° [horizontal(131°) vertical (96 °)] Min. Illumination: 1 lux, Napajanje 12V ~ 24V (cigarette plug), potrošnja: 2.8W, 80 mm X 50 Ø , 100g	AMD-XB1000	239,00	
	DVR za 1 kanal za ugradnju u vozila, podržava 1x2GB SD memory card (support SDHC), brzina prikaza/snimanja 30fps u rezoluciji 640*480 ili 320*240, JPEG kompresija, snimanje kontinualno, po događajima ili pritiskom na panik taster, G-senzor, RTC, PC program za analizu, Google Earth integration, sa integrisanom kamerom 1/4" CMOS Digital Sensor 310K pixels, Angle of View: 170° [horizontal(131°) vertical (96 °)] Min. Illumination: 1 lux, Napajanje 12V ~ 24V (cigarette plug), potrošnja: 2.8W, 80 mm X 50 Ø , 100g	AMD-XB1000 Plus	299,00	
	DVR za 1 kanal za ugradnju u vozila, podržava 1x2GB SD memory card (support SDHC), brzina prikaza/snimanja 30fps u rezoluciji 640*480 ili 320*240, JPEG kompresija, snimanje kontinualno, po događajima ili pritiskom na panik taster, G-senzor, RTC, PC program za analizu, Google Earth integration, sa integrisanom kamerom 1/4" CMOS Digital Sensor 310K pixels, Angle of View: 90° [horizontal(131°) vertical (96 °)] Min. Illumination: 1 lux, Napajanje 12V ~ 24V (cigarette plug), potrošnja: 2.8W, 80 mm X 50 Ø , 100g	AMD-XB1000 Plus with 90° lens	299,00	
	DVR za 3 kanala za ugradnju u vozila, podržava 32GB SD memory card (support SDHC), MPEG4 & MJPEG kompresija, Display Resolution - 720x576(PAL), 720x480(NTSC) Display Speed - Real Time, Record Resolution - PAL: 720x576, 720x288 NTSC: 720x480, 720x240 Record Speed - PAL: 25fps @ 720x576, 50fps @ 720x288 NTSC: 30fps @ 720x480, 60fps @ 720x240, snimanje kontinualno, po događajima ili pritiskom na panik taster, G-senzor, 3 alarmna ulaza, mikrofoni, eksterna GPS antena, eksterni panik taster, impulsni ulaz za brzinu, RTC, daljinski upravljač, 1 Power cable + 1 A/V out cable, PC program za analizu, Google Earth integration, Napajanje 12V ~ 24V (cigarette plug) 70mm X 99 mm X 21mm, 100g	AMD-XB3000	329,00	
	DVR za 2 kanala za ugradnju u vozila, podržava 32GB SD memory card (support SDHC), MPEG4 & MJPEG kompresija, Display Resolution - 720x576(PAL), 720x480(NTSC) Display Speed - Real Time Display, Record Resolution - PAL: 720x576, 720x288 NTSC: 720x480, 720x240 Record Speed - PAL: 25fps @ 720x576 50fps @ 720x288 NTSC: 30fps @ 720x480 60fps @ 720x240, snimanje kontinualno, po događajima ili pritiskom na panik taster, G-senzor, 2 alarmna ulaza, mikrofoni, eksterna GPS antena, eksterni panik taster, impulsni ulaz za brzinu, RTC, daljinski upravljač, 1 Power cable + 1 A/V out cable, Power module (Delayed shut down)+ Housing ,PC program za analizu, Google Earth integration, podržava kamere na 12VDC, Napajanje 12V ~ 24V (cigarette plug) 155x130x24mm, 470g	AMD-BX3000Duo	379,00	
Kamere za ugradnju u vozila				
	CMOS kamera za BX3000, 1/4" CMOS Digital Sensor 310K pixels Angle of View: 170° [horizontal(131°) vertical (96 °)] Effective Pixel: 648 (H) x 488 (V) (NTSC/PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 1 lux, radna temperatura: -20°C ~ 60°C, ulazni napon: 5V, 30mm x 35mm x 25mm	AMD-DTR-100	69,00	
	CCD kamera za BX3000 1/3" Sony Super HAD CCD II Angle of View: 90° Effective Pixel: 510(H) X 492(V) (NTSC), 500(H) X 582(V) (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 0.1 lux, radna temperatura: -20°C ~ 60°C, ulazni napon: 5V, 43mm x 38mm x 35mm	AMD-STR-100	99,00	
	CCD kamera za BX3000 1/3" Sony Super HAD CCD II Angle of View: 145° Effective Pixel: 510(H) X 492(V) (NTSC), 500(H) X 582(V) (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: IR LED On 0 lux, radna temperatura: -20°C ~ 60°C, ulazni napon: 5V, 43mm x 38mm x 35mm	AMD-STR-100IR	104,00	
	CCD kamera za BX3000 1/3" Sony Super HAD CCD II Angle of View: 90° Effective Pixel: 510(H) X 492(V) (NTSC), 500(H) X 582(V) (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 0.1 lux, radna temperatura: -20°C ~ 60°C, ulazni napon: 12V, 43mm x 38mm x 35mm	AMD-STR-100_12V	99,00	
	CCD kamera za BX3000 1/3" Sony Super HAD CCD II Angle of View: 145° Effective Pixel: 510(H) X 492(V) (NTSC), 500(H) X 582(V) (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: IR LED On 0 lux, radna temperatura: -20°C ~ 60°C, ulazni napon: 12VDC, Max.320mA(LED ON) 43mm x 38mm x 35mm	AMD-STR-100IR_12V	104,00	

	Zoom kamera za policijske automobile, Sony FCB-EX20D Zoom module, 1/3" Super HAD CCDII, laka za upotrebu, One-Touch Smart Zoom-in/out taster, 10x Optical Zoom (Auto focus, Auto iris and Zoom tracking function) visoka rezolucija (530TV Lines) Day & Night funkcija	AMD-DTR-700N/P ZOOM CAMERA	760,00	
	CMOS Rear View kamera, vodootporna - IP 68, 1/4" Hi Resolution CMOS, Angle of View: 162°, Effective Pixel: (H)640x(V)480 (NTSC / PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 1 lux, radna temperatura: -30°C ~ 85°C, ulazni napon: DC 12V (±20%) mala potrošnja: Max. 35mA, 28x29x26mm, 113g, sa produžnim kablom 8m	AMD-NEW STR-131	99,00	
	CCD Rear View kamera, vodootporna -IP 67, 1/4" Sony Super HAD CCD, Angle of View: 159° Effective Pixel: (H)510x(V)492 (NTSC) (H)500x(V)582 (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 0.5 lux, radna temperatura: -20°C ~ 60°C, ulazni napon: DC 12V (±20%) mala potrošnja: 80mA, Φ18.6 x 22.4 mm, sa produžnim kablom 8m	AMD-NRV-001	106,00	
	CCD Rear View kamera, vodootporna -IP 67, 1/4" Sony Super HAD CCD, Angle of View: 159° Effective Pixel: 510(H) X 492(V) (NTSC), 500(H) X 582(V) (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 0.5 lux, radna temperatura: -20°C ~ 60°C, ulazni napon: DC 12V (±20%) mala potrošnja: 80mA, 25x29x27mm, sa produžnim kablom 8m	AMD-NRV-001M	110,00	
	CMOS Rear View kamera, vodootporna -IP 67, 1/4" Hi Resolution CMOS, Angle of View: 162° Effective Pixel: (H)640x(V)480 (NTSC / PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 1 lux, radna temperatura: -30°C ~ 85°C, ulazni napon: DC 12V (±20%) mala potrošnja: Max. 35mA, 29x34x29mm, 80g, sa produžnim kablom 8m	AMD-STR-132A	84,00	
	CMOS Rear View kamera, vodootporna - IP 67 1/4" Hi Resolution CMOS Angle of View: 162° Effective Pixel: (H)640x(V)480 (NTSC / PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 1 lux, radna temperatura: -30°C ~ 85°C, ulazni napon: DC 12V (±20%) mala potrošnja: Max. 35mA, 29x34x42mm, 113g, sa produžnim kablom 8m	AMD-STR-132B	84,00	
	CCD kamera, vodootporna - IP 67, 1/3" Sony Super HAD CCD (High Sensitivity CCDII) Angle of View: 120° Effective Pixel: (H)510x(V)492 (NTSC) (H)500x(V)582 (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 0.1 lux, radna temperatura: -20°C ~ 60°C, ulazni napon: DC 9 ~ 28V mala potrošnja: 110mA, 64x45x62mm, bez produžnog kabla	AMD-STR-200	118,00	
	CCD Camera, vodootporna -IP 67, 1/3" Sony Super HAD CCD (High Sensitivity CCDII) Angle of View: 120° Effective Pixel: (H)510x(V)492 (NTSC) (H)500x(V)582 (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: IR LED On 0 lux, dome IC iluminatora: 10m, radna temperatura: -20°C ~ 60°C, ulazni napon: DC 9 ~ 28V, potrošnja: 170mA, 64x45x62mm, bez produžnog kabla	AMD-STR-200IR	120,00	
	CCD Camera, vodootporna -IP 67, 1/3" Sony Super HAD CCD (High Sensitivity CCDII) Angle of View: 120° Effective Pixel: 510(H) X 492(V) (NTSC), 500(H) X 582(V) (PAL) Video out: 1.0 Vp-p (Composite) Min. Illumination: 0.1 lux, radna temperatura: -20°C ~ 60°C, ulazni napon: DC 12V mala potrošnja: 70mA, 40x50x43mm, bez produžnog kabla	AMD-STR-220	100,00	
	Kolor dome kamera za ugradnju u vozila, Sony Super HAD CCD 1/3" (High Sensitivity CCD II) Angle of View: 90°, visoka rezolucija: 550TV Lines Video out: 1.0 Vp-p (Composite) Min. Illumination: 0.1 lux, radna temperatura: -20°C ~ 60°C, ulazni napon DC 12V, Φ80 x 61 mm	AMD-STC-300HD	148,00	
	Kolor dome kamera za ugradnju u vozila, Sony Super HAD CCD 1/3" (High Sensitivity CCD II) Angle of View: 90°, visoka rezolucija: 550TV Lines Video out: 1.0 Vp-p (Composite) Min. Illumination: 0.1 lux, radna temperatura: -20°C ~ 60°C, ulazni napon DC 12V Φ80mm x 55 mm	AMD-DS-2070	136,00	
Prateća oprema				
	Memorijska kartica za arhiviranje video snimka SDHC 32GB Class 10	TS32GSDHC10	65,00	
	Napojni kabl - cigarette jack	AMD-CPWR-100	6,00	
	Napojni kabl - fuse connection	AMD-DPWR-100	6,00	
	Napojni kabl - fuse connection (Safe Power)	AMD-DPWR-200	30,00	
	Napojni kabl - fuse connection (Safe Power)	AMD-DPWR-300	31,00	
	Duplo lepljiva traka 50PCS	AMD-S-STK	20,00	
	Držači kablova 100PCS	AMD-S-WSC	20,00	
	Čitač SD kartica	AMD-S-RDR	2,00	
	Zaštitni okvir sa ključem za BX1000 služi za sprječavanje vađenja SD kartice iz uređaja bez ključa koji ima ovlašćeno lice	AMD-LNB-100	30,00	
	Eksterni mikrofon za BX3000, osetljivost : -36±5dB, 2.2Kohm, 0dB=1V/Pa 1KHz Impedance : 2.2K Ohm@1KHz Max. ulazni napon: 10V, Frequency : 100~10,000Hz, mala potrošnja: 0.5mA, radna temperatura: -40°C ~ 85°C, Dim.: Φ9.7 x 5.0mm	AMD-MIC-100	6,00	
	Metalno kućište za BX3000, Dim. 155.00 x 130.00 x 24.00 mm, 330g	AMD-SH-100	30,00	
	LCD kolor monitor 7"(17.5cm) projekcija 16:9 digital wide TFT, Video NTSC/PAL, dva AV ulaza, stereo zvučnici, dva video kanala, auto rear view funkcija, auto dimer, DC12V, 184x115x20mm	AMD-DSM-720	190,00	