








Navedene cene su bez PDVa. Radi ostvarivanja POPUSTA, kontaktirajte nas!











































Adresabilne centrale, detektori i oprema - GLT Zeta

	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa jednom petljom kapaciteta 64 detektora u petlji, podržava samo adr. Sirene, fault out 28V, fire out 28V, Metalno kućište 355x275x100mm	GLT-SP-64/M	425,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa jednom petljom kapaciteta 126 detektora u petlji, podržava samo adr. Sirene, fault out 28V, fire out 28V, Metalno kućište 355x275x100mm	GLT-SP-126/M	475,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa dve petlje, kapaciteta 126 adresa po petlji, nije proširiva, podržava samo adr. Sirene, fault out 1A, fire out 1A, Metalno kućište 485x395x120mm	GLT-SP-252/M	550,00	
	Serijski paralelni tablo sa LCD displejem za centrale iz serije SP-64/126/252, služi samo za nadgledanje ali ne i kontrolisanje sistema, 355x275x70mm	GLT-REP-AD	250,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa LCD displejem, sa jednom petljom, proširiva do četiri petlje, kapaciteta 126 adresa u petlji, izlaz za sirene 2x1A, fault out 1A, fire out 1A, 410x480x144mm	GLT-PR-AL/1	1.245,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa LCD displejem, sa dve petlje, proširiva do četiri petlje, kapaciteta 126 adresa u petlji, izlaz za sirene 2x1A, fault out 1A, fire out 1A, 410x480x144mm	GLT-PR-AL/2	1.425,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa LCD displejem, sa tri petlje, proširiva do četiri petlje, kapaciteta 126 adresa u petlji, izlaz za sirene 2x1A, fault out 1A, fire out 1A, 410x480x144mm	GLT-PR-AL/3	1.615,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa LCD displejem, sa četiri petlje, kapaciteta 126 adresa u petlji, izlaz za sirene 2x1A, fault out 1A, fire out 1A, 410x480x144mm	GLT-PR-AL/4	1.799,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa LCD displejem, sa pet petlji, proširiva do osam petlji, kapaciteta 126 adresa u petlji, izlaz za sirene 4x1A, fault out 1A, fire out 1A, aux 2x500mA, 960x480x144mm	GLT-PR-AL/5	3.050,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa LCD displejem, sa šest petlji, proširiva do osam petlji, kapaciteta 126 adresa u petlji, izlaz za sirene 4x1A, fault out 1A, fire out 1A, aux 2x500mA, 960x480x144mm	GLT-PR-AL/6	3.229,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa LCD displejem, sa sedam petlji, proširiva do osam petlji, kapaciteta 126 adresa u petlji, izlaz za sirene 4x1A, fault out 1A, fire out 1A, aux 2x500mA, 960x480x144mm	GLT-PR-AL/7	3.410,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa LCD displejem, sa osam petlji, kapaciteta 126 adresa u petlji, izlaz za sirene 4x1A, fault out 1A, fire out 1A, aux 2x500mA, 960x480x144mm	GLT-PR-AL/8	3.600,00	
	Modul za proširenje za centrale serije PR (Premier) za jednu adresabilnu petlju	GLT-AL-LP	190,00	
	Premier AL Repeater tablo sa LCD displejem za centrale ZT-PR-AL	GLT-REP-AL/P	870,00	
	Premier AL Global Network Repeater tablo sa LCD displejem za centrale ZT-PR-AL	GLT-REP-AL/G	1.210,00	
	Mrežna kartica za umrežavanje PP centrala serije PR (Premier)	GLT-PR-AL/NW	495,00	
	Alarm Manager Graphic Package (Includes Computer Hardware + 15" Monitor)	GLT-AL-AM	3.663,00	
	TCP/IP komunikator	GLT-IP-COM	231,00	
	GSM komunikator za slanje SMS poruke o stanju sistema	GLT-GSM-COM	550,00	

	Adresabilni ulazni modul za centrale Premier, Operating Voltage 17 – 33V DC, Alarm Current 2.9mA, Fault Current 2.8mA, Isolating Current 7.3mA, 127 x 88 x 57mm	GLT-ZIU	35,00	
	Adresabilni ulazno izlazni modul za centrale Premier, Operating Voltage 17 – 33V DC, Alarm Current 10.6mA, Fault Current 2.8mA, Isolating Current 7.3mA, 127 x 88 x 59mm	GLT-ZIUU	45,00	
	Adresabilni modul za povezivanje konvencionalnih sirena, Operating Voltage 17 – 33V DC, Alarm Current 10.6mA (10mA +sounder load from PSU) Fault Current 2.8mA (10mA from PSU) Isolating Current 7.3mA (6.8 mA from ext PSU), 127 x 88 x 59mm	GLT-ZSCC	61,60	
	Modul za priključenje konvencionalnih detektora na adresabilnu petlju, Operating Voltage 1 – 33V DC, Quiescent Current 800uA (40 mA from ext PSU), Alarm Current 780uA (105mA from PSU) (4 circuits) Fault Current 820uA (175mA from PSU) (Max for 4 circuits) Isolating Current 7.3mA (40 mA from ext PSU) 127 x 88 x 59 mm	GLT-ZT2M	66,00	
	Adresabilni dualni optičko-termički detektor, Operating Voltage 17-28V DC, Alarm Current 2.3mA, vreme reagovanja 30 sec. Pokriva prostor 100m2, DIFT approved, complies fully to EN54 parts 5 & 7	GLT-FEA0H2000	30,00	
	Adresabilni optički detektor, Operating Voltage 17-28V DC, Alarm Current 2.3mA, vreme reagovanja 10 sec. Pokriva prostor 100m2, DIFT approved, complies fully to EN54 parts 5 & 7	GLT-FEA0E2000	25,00	
	Adresabilni termo diferencijalni detektor, takođe radi i kao detektor fiksne temperature preko 57°C, Operating Voltage 17-28V DC, Alarm Current 2.4mA, vreme reagovanja 30 sec. Pokriva prostor 50m2, DIFT approved, complies fully to EN54 parts 5 & 7	GLT-FEAHE2000	22,00	
	Adresabilni detektor visoke temperature preko 90°C, Operating Voltage 17-28V DC, Alarm Current 2.4mA, vreme reagovanja 30 sec. Pokriva prostor 50m2, DIFT approved, complies fully to EN54 parts 5 & 7	GLT-FEAHHE2000	23,00	
	Standardna baza za adresabilne detektore, Operating Voltage 17-28V DC	GLT-FE-CB	3,30	
	Baza sa izolatorom kratkog spoja, Operating Voltage 17-28V DC	GLT-FEA-IB	15,40	
	Ručni javljač požara - adresabilni, resetujući, Input Voltage 17-33V DC, Quiescent Current 1.5 mA, Alarm Current 1.5 mA, Complies fully to EN54 part 11, IP 43	GLT-CP2/AD	31,90	
	Ručni javljač požara - adresabilni, resetujući, Input Voltage 17-33V DC, Quiescent Current 1.5 mA, Alarm Current 1.5 mA, Complies fully to EN54 part 11, IP 67	GLT-CP2/AD/WP	52,80	
	Adresabilna protivpožarna sirena za unutrašnju ili spoljnu montažu, IP65, 16mA, 103dB, 124 x 130 x 100mm	GLT-ZAMT/R	56,10	
	Adresabilna protivpožarna sirena sa strob svetlom za unutrašnju ili spoljnu montažu, IP65, 16mA, 103dB, 124 x 130 x 100mm	GLT-ZAMTF/R	77,00	
	Paralelni svetlosni indikator - adresabilni - za GLT-SP-64/126/252/M	GLT-ZTA-LE2	16,50	
	Paralelni svetlosni indikator - adresabilni (2-10 adresa)	GLT-LE2-10	24,20	
	Paralelni svetlosni indikator - adresabilni - za centrale ZT-PR-AL serije	GLT-ZTA-LE3	9,00	
	Adresabilni reflective beam detektor (5-50m), potrošnja 5mA u normalnom stanju, 9mA u alarmnom stanju	GLT-ZT-50RA	616,00	
	Adresabilni reflective beam detektor (50-100m), potrošnja 5mA u normalnom stanju, 9mA u alarmnom stanju	GLT-ZT-100RA	660,00	









Adresabilne centrale, detektori i oprema - Nittan - Evolution













	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa jednom petljom, proširiva do dve petlje, kapaciteta 254 adrese u petlji	NTN-EVA-2-1	880,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa dve petlje, kapaciteta 254 adrese u petlji	NTN-EVA-2-2	1.040,00	

	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa jednom petljom, proširiva do četiri petlje, kapaciteta 254 adrese u petlji	NTN-EVA-4-1	1.299,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa dve petlje, proširiva do četiri petlje, kapaciteta 254 adrese u petlji	NTN-EVA-4-2	1.485,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa tri petlje, proširiva do četiri petlje, kapaciteta 254 adrese u petlji	NTN-EVA-4-3	1.650,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa četiri petlje, kapaciteta 254 adrese u petlji	NTN-EVA-4-4	1.799,00	
	Paralelni tablo sa LCD displejem za EVA-2 & EVA-4 centrale	NTN-EV-Repeater Panel	810,00	
	Štampač za EVA-2 & EVA-4 centrale	NTN -EV-Internal Printer	365,00	
	Adresabilni ulazni izlazni modul	NTN-EV-AIO21	99,00	
	Modul za sirenu sa jednim izlazom, 1A, sa nadzorom eksternog napajanja	NTN-EV-SM L/P	68,00	
	Modul za konvencionalnu zonu sa dva ulaza, Ulaz #1 max ~5 konvencionalnih detektora ili 250 uA, Ulaz #2 max 1 x NS-ISOLATOR i 10 x ST-I-IS	NTN-EV-AIN1 L/P	85,00	
	Ulazni modul za Sprinkler sa dva ulaza (NO/NC)	NTN-EV-AIN2 L/P	85,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa jednom petljom, proširiva do šest petlji, kapaciteta 254 adrese u petlji, mogućnost umrežavanja više EVA-1 centrale pomoću RS485 magistrale, (max. 1524 adrese i 192 zones kod centrale sa 6 petlji), 4 programabilna relejna izlaza, 2 izlaza za sirene, integrisan RS232, veliki LCD grafički displej	NTN-EVA-1	1.369,00	
	Paralelni tablo sa LCD displejem za EVA-1centralu	NTN-EVA-1-MRP	684,00	
	Modul za adresabilnu petlju za EVA centrale	NTN-EV-Loop Card	210,00	
	Modul za konvencionalnu zonu za EVA centrale	NTN-EV-Zone Card	228,00	
	Adresabilni ulazni modul za EVA-1centralu	NTN-EV-Input Card	171,00	
	Relejni modul sa 8 relejnih izlaza, 24VDC za EVA-1centralu	NTN-EV-8 RC 24V	116,00	
	Relejni modul sa 8 relejnih izlaza, 220VAC za EVA-1centralu	NTN-EV-8 RC 220V	171,00	
	Modul za sirenu za EVA-1centralu	NTN-EV-5-Sounder Card	164,00	
	Daljinski programator za Evolution detektore	NTN-EV- Adres.Prog.	225,00	
	Štampač za EVA-1 centralu	NTN-EVA-1 -ITP	387,50	
	EVA-1 panel programming software	NTN-EVA-1 Con/Software	875,00	



























	Analogno adresabilni optički detektor	NTN-EV-P	33,50	
	Analogno adresabilni dualni optički detektor	NTN-EV-DP	54,00	
	Analogno adresabilni termički detektor	NTN-EV-H-CS	37,50	
	Analogno adresabilni multi - optičko-termički detektor sa mogućnošću odabira moda detekcije samo kao optički ili samo kao termički	NTN-EV-PH	44,00	
	Adresabilni termodiferencijalni detektor	NTN-EV-H-A1R	37,50	
	Standardna baza za sve Nittan detektore	NTN-UB-4	2,15	
	Baza sa izolatorom kratkog spoja	NTN-S.C.I.-5	21,70	
	Izolator petlje	NTN-S.C.I.-6	28,50	
	Dozna za izolator petlje	NTN-S.C.I.-6 Box	1,40	
	Izolator petlje	NTN-EV-SCI	84,00	
	Ručni javljač požara - adresabilni	NTN-EV-MCP-IP24	39,50	
	Vodootporni adresabilni ručni javljač	NTN-EV-MCP-IP67	96,00	
	Adresabilna protivpožarna sirena	NTN-EV-ABS L/ P	49,00	
	Baza za adresabilne protivpošarne sirene	NTN-STB4-EV-AB	4,60	
	UV detektor plamena	NTN-EV-UV	330,00	
	Zidni nosač za UV detektor plamena	NTN-NFD-68P	57,00	































Adresabilne centrale Advance - Nittan Evolution protokol

	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa jednom petljom, proširiva do dve petlje, kapaciteta 254 adrese u petlji, 200 zona dojave, sa dva programabilna relejna izlaza, dva programabilna izlaza za sirene, dva programabilna open collector izlaza i šest programabilnih digitalnih izlaza, poseduje grafički displej	ADV-MX4201	880,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa dve petlje, kapaciteta 254 adrese u petlji, 200 zona dojave, sa dva programabilna relejna izlaza, dva programabilna open collector izlaza i šest programabilnih digitalnih izlaza, poseduje grafički displej	ADV-MX4202	1.155,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa jednom petljom, proširiva do četiri petlje, kapaciteta 254 adrese u petlji, 200 zona dojave, sa dva programabilna relejna izlaza, četiri programabilna izlaza za sirene, dva programabilna open collector izlaza i šest programabilnih digitalnih izlaza, poseduje grafički displej	ADV-MX4401	1.399,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa dve petlje, proširiva do četiri petlje, kapaciteta 254 adrese u petlji, 200 zona dojave, sa dva programabilna relejna izlaza, četiri programabilna izlaza za sirene, dva programabilna open collector izlaza i šest programabilnih digitalnih izlaza, poseduje grafički displej	ADV-MX4402	1.550,00	















	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa tri petlje, proširiva do četiri petlje, kapaciteta 254 adrese u petlji, 200 zona dojave, sa dva programabilna relejna izlaza, četiri programabilna izlaza za sirene, dva programabilna open collector izlaza i šest programabilnih digitalnih izlaza, poseduje grafički displej	ADV-MX4403	1.750,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa četiri petlje, kapaciteta 254 adrese u petlji, 200 zona dojave, sa dva programabilna relejna izlaza, četiri programabilna izlaza za sirene, dva programabilna open collector izlaza i šest programabilnih digitalnih izlaza, poseduje grafički displej	ADV-MX4404	1.950,00	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala proširiva do osam petlji, kapaciteta 254 adrese u petlji, 200 zona dojave, sa četiri programabilna relejna izlaza, osam programabilnih izlaza za sirene, četiri programabilna open collector izlaza i dvanaest programabilnih digitalnih izlaza, poseduje grafički displej, poseduje mrežnu karticu	ADV-MX4800	3.815,00	
	Paralelni tablo sa Grafičkim LCD displejem	ADV-MX4020	639,00	
	Mrežna kartica za umrežavanje centrala razdaljine do 1,5km	ADV-MXP003F	215,00	
	Mrežna kartica za umrežavanje centrala razdaljine do 20km	ADV-MXP009F	535,00	

Adresabilne centrale, detektori i oprema - Honeywell - Cooper











	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa 1 petljom, sa Touch Screen displejom - 200 elemenata po petlji	HON-CSIT1100	1.037,20	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa 2 petlje, sa Touch Screen displejom - 200 elemenata po petlji	HON-CSIT1200	1.555,20	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa 2 petlje, sa grafickim displejom - 200 elemenata po petlji	HON-CSIT2000/G	1.243,40	
	Analogno adresabilna mikroprocesorska protivpožarna alarmna centrala sa 2 petlje proširiva do 4, sa Touch screen displejom - 200 elemenata po petlji	HON-CSIT3000/2/G	2.047,10	
	Ekspanziona kartica sa 2 petlje, za centrale CSIT3000/2/G	HON-CSYPCB2148	336,60	
	Delitelj petlje 1/4	HON-CSYPCB2222	130,40	
	Mrežna kartica za panel CSIT3000	HON-CSDF6000/NC	298,10	
	Adresabilni ulazno/izlazni modul (3 ulaza/3 izlaza)	HON-CSCIO351	185,90	
	Adresabilni ulazni mikro modul (1 ulaz)	HON-CSMCIM	36,30	
	Adresabilni izlazni mikro modul (1 izlaz)	HON-CSMCOMS	43,50	
	SPUR modul	HON-CSCSI350	95,20	
	Adresabilni modul za konvencionalne detektore i sirene	HON-CSCSUM355	190,40	
	Paralelna konzola za centralu CSIT3000- povezivanje u petlju	HON-CSIT3000PR	634,80	

	Paralelna konzola za centralu CSIT3000- povezivanje u mrežu centrala	HON-CSIT3000PR/NC	952,10	
	Printer za centrale CSIT3000	HON-CSDF6000/PKIT	399,00	
	Analogno adresabilni optički detektor sa ugrađenim izolatorom kratkog spoja u sebi	HON-CSCAP320	36,30	
	Analogno adresabilni termički ili termodiferencijalni detektor (izbor korisnika pri programiranju) sa ugrađenim izolatorom kratkog spoja u sebi	HON-CSCAH330	31,70	
	Analogno adresabilni optičko-termički detektor sa ugrađenim izolatorom kretkog spoja u sebi	HON-CSCAPT340	40,80	
	Baza za adresabilne detektore	HON-CSCAB300	3,60	
	Vodootporni adapter za standardnu bazu	HON-CSBAR3000	6,80	
	Ručni javljač požara - adresabilni (uzidna montaža)	HON-CSCBG370	46,60	
	Ručni javljač požara - adresabilni (nazidna montaža)	HON-CSCBG370/S	54,40	
	Paralelni svetlosni indikator	HON-CSCIR301	7,80	
	Paralelni indikator - vodootporni - IP65	HON-CSCIR301-WP	10,40	
	Paralelni svetlosni indikator - adresabilni	HON-CSMRIAD	33,20	
	Adresabilna protivpožarna sirena - IP42	HON-CSCAS381	86,10	
	Adresabilna protivpožarna sirena integrisana u podnožje detektora	HON-CSCAS380	77,10	
	Adresabilna protivpožarna sirena sa strob svetlom - IP65	HON-CSCASB383	100,90	





























Konvencionalne centrale, detektori i oprema - GLT Zeta

	Konvencionalna protivpožarna centrala sa dve zone, neproširiva, 1 modul gašenja	BNT-J 408-2	165,00	
	Konvencionalna protivpožarna centrala sa četiri zone, neproširiva, 1 modul gašenja	BNT-J 408-4	188,00	
	Konvencionalna protivpožarna centrala sa osam zona, neproširiva, 1 modul gašenja	BNT-J 408-8	210,00	
	Osmozonska PP centrala, proširiva da 24 zone, LED indikacija, 4x250mA izlaz za sirene, požarni relejni izlaz, relejni izlaz za greške	GLT-PMP8	429,00	
	PP centrala sa 16 zona, proširiva da 24 zone, LED indikacija, 4x250mA izlaz za sirene, požarni relejni izlaz, relejni izlaz za greške	GLT-PMP16	562,50	
	PP centrala sa 24 zone, LED indikacija, 4x250mA izlaz za sirene, požarni relejni izlaz, relejni izlaz za greške	GLT-PMP24	561,00	
	Modul za proširenje za centralu ZT-PMP8 sa 8 zona	GLT-PM+8	66,00	





	Paralelni tablo za PMP 8/16/24 centrale	GLT-PMP-REP	396,00	
	PP centrala sa 32 zone, proširiva da 48 zone, LED indikacija, 4x400mA izlaz za sirene, požarni relejni izlaz, relejni izlaz za greške, 675 x 480 x 135 mm	GLT-PMP48/32	880,00	
	PP centrala sa 48 zona, LED indikacija, 4x400mA izlaz za sirene, požarni relejni izlaz, relejni izlaz za greške, 675 x 480 x 135 mm	GLT-PMP48/48	1.100,00	
	Paralelni tablo za PMP 48 centrale	GLT-PMP48-REP	495,00	
	Zonska output kartica za konvencionalne centrale	GLT-CONV-ZC	53,00	
	Konvencionalni optički detektor, Operating Voltage 9-33V DC, Alarm Current 53mA, vreme reagovanja 10 sec. Pokriva prostor 100m2, DIFT approved, design standard EN54 part 7	GLT-FEOE2000	11,00	
	Konvencionalni detektor visoke temperature preko 90°C, Operating Voltage 9-33V DC, Alarm Current 34mA, vreme reagovanja 10 sec. Pokriva prostor 50m2, DIFT approved, design standard EN54 part 5	GLT-FEFHE2000	10,50	
	Konvencionalni termo diferencijalni detektor, takođe radi i kao detektor fiksne temperature preko 57°C, Operating Voltage 9-33V DC, Alarm Current 34mA, vreme reagovanja 10 sec. Pokriva prostor 50m2, DIFT approved, design standard EN54 part 5	GLT-FEHE2000	10,00	
	Konvencionalni dualni optičko-termički detektor, Operating Voltage 17-20V DC, Alarm Current 17mA, Pokriva prostor 100m2, DIFT approved, design standard EN54	GLT-FEOH2000	15,50	
	Standardna baza za konvencionalne detektore, Operating Voltage 17-28V DC	GLT-FE-CB	3,30	
	Konvencionalna protivpožarna sirena 100dB, 35mA	GLT-ZST/8R	20,00	
	Konvencionalna protivpožarna sirena za unutrašnju ili spoljnu montažu, IP65, 16mA, 103dB, 124 x 130 x 100mm	GLT-ZMT/8R	22,00	
	Konvencionalna protivpožarna sirena sa strob svetlom za unutrašnju ili spoljnu montažu, IP65, 16mA, 103dB, 124 x 130 x 100mm	GLT-ZMTF/8R	37,50	
	Konvencionalni ručni javljač požara - resetujući sa zaštitnim staklom	GLT-CP2	12,00	
	Vodootporni konvencionalni ručni javljač požara - resetujući	GLT-CP2/WP	35,00	
	Konvencionalni ručni javljač u plavoj boji	GLT-CP2B	12,00	
	konvencionalni ručni javljač u žutoj boji	GLT-CP2Y	12,00	
	Paralelni svetlosni indikator, IP43	GLT-ZT/LE8	5,50	
	Paralelni svetlosni indikator	GLT-ZT-RL	4,50	
	UV detektor plamena, ugao detekcije 120	GLT-FEUV2000	180,00	
	Konvencionalni reflective beam detektor (5-50m)	GLT-ZT-50RZ	550,00	





































	Konvencionalni reflective beam detektor (50-100m)	GLT-ZT-100RZ	620,00	
	Konvencionalni Auto-aligning beam detektor 50m	GLT-ZT-5000R	561,00	
	Konvencionalni Auto-aligning beam detektor 100m	GLT-ZT-5000R/100	695,00	
	UV-IR detektor plamena	GLT-VS-200P	1.250,00	
	UV-IR detektor plamena sa protiveksplozivnom zaštitom	GLT-VS-200EX	3.600,00	














Konvencionalni detektori i oprema - Nittan - Evolution

	Konvencionalni optički detektor dima, EN54-7	NTN-EVC-P	17,00	
	Termički detektor brzog odziva - 54-56 stepeni	NTN-EVC-H-A1	15,00	
	Termički detektor brzog odziva - 54-70 stepeni	NTN-EVC-H-A2	16,50	
	Termički detektor brzog odziva - 69-85 stepeni	NTN-EVC-H-B	15,00	
	Termički detektor brzog odziva - 84-100 stepeni	NTN-EVC-H-C	13,25	
	Optički dualni detektor	NTN-EVC-DP	44,00	
	Standardna baza za sve Nittan detektore	NTN-UB-4	2,15	
	Konvencionalni reflective beam detektor (5-100m)	NTN-EVC-BD	524,40	
	Komora za analizu uzoraka vazduha iz ventilacionog kanala	NTN-STA-D5	92,00	
	Cev za uzimanje uzorka dužine 0.6m	NTN-STA-VP-0.6	16,50	
	Cev za uzimanje uzorka dužine 1.5m	NTN-STA-VP-1.5	49,00	
	Ručni javljač požara- resetujući	NTN-NCKP-470	10,00	
	Paralelni indikator	NTN-STA-R1	12,00	
	Infracrveni "light beam" (linijski) detektor podesivog rastojanja 5-100m	NTN-FIRERAY2000	681,00	

Konvencionalni detektori - Honeywell -Cooper i System Sensor

	Fotoelektrični detektor	HON-ECO1003	29,50	
	Fotoelektrični i termički detektor	HON-ECO12	29,00	

	Termodiferencijalni detektor	HON-ECO1005	19,00	
	Termički detektor brzog odziva - 58 stepeni	HON-ECO1005T	19,00	
	Standardna baza	HON-ECO1000B	6,50	
	Standardna baza sa relejnim izlazom 12V (latching)	HON-ECO1000BREL12L	20,00	
	Konvencionalni optički detektor	HON-CSCPD320	23,20	
	Konvencionalni termički detektor	HON-CSCHT390	17,20	
	Standardna baza za konvencionalne detektore	HON-CSCDBB300	3,60	
Konvencionalni pribor i oprema - Ostali proizvođači				
	Konvencionalni ručni javljač požara	AMD-FA-102	8,00	
	Konvencionalni ručni javljač požara	AMD-FA-103	10,00	
	Konvencionalni ručni javljač požara	AMD-FA-1051	11,60	
	Konvencionalni ručni javljač požara - resetujući	AMD-FA-1052	10,00	
	Konvencionalni ručni javljač požara - resetujući	AMD-FA-1053	13,50	
	Konvencionalni ručni javljač požara - resetujući	AMD-FA-1054	14,50	
	Protivpožarna sirena sa strob svetlom 24V, 120mA	AMD-PSL-82	22,60	
	Protivpožarna sirena sa strob svetlom 24V, 300mA	AMD-PSL-83	19,00	
	Protivpožarna piezo sirena sa strob svetlom 24V, 300mA	AMD-PSL-85	9,99	
	Protivpožarna piezo sirena sa strob svetlom 24V, 55mA	AMD-PSL-81	10,60	
Honeywell	Konvencionalna protivpožarna sirena, 15mA	HON-EMA1224BR	21,20	
Honeywell	Visoko profilna baza za sirene	HON-ESBR	4,00	Honeywell
Honeywell	Visoko profilna baza za sirene IP66	HON-ESBRS	6,00	Honeywell
	Protivpožarno crveno rotaciono svetlo 24V	AMD-SL-81	11,60	
	Akumulator 12V, 12Ah	AMD-AKB-12	38,00	

	Akumulator 12V, 14Ah	AMD-AKB-14	39,00	
	Akumulator 12V, 18Ah	AMD-AKB18	49,00	
	Akumulator 12V, 24Ah	AMD-AKB24	69,00	
	Akumulator 12V, 26Ah	AMD-AKB-26	85,00	
	Akumulator 12V, 33Ah	AMD-AKB-33	102,00	
	Akumulator 12V, 38Ah	AMD-AKB-38	126,00	
Honeywell	Univerzalni pribor za demontažu i testiranje detektora	HON-SOLO811	1.242,00	
Honeywell	Tester sensora	HON-NB-SOLO A3	17,00	